

WEISSES HAUS KUNSTHARZ-ROLLPUTZ



Designs and protects walls and façades with a plaster which can be rolled on like paint.

Product characteristics

- | High quality latex plaster for rolling on.
- | With real Italian marble.
- | Produces a coating that is 10 times thicker than paint when rolled on. It is therefore considerably more resistant and durable.
- | Snow white, weatherproof, shock-resistant, hard-wearing, permeable by water vapour.
- | Free of solvents and softeners in accordance with VdL directive 01.
- | Grain: 0.5 mm.

Practical tip: During direct application with a roller, the roller must be properly soaked in plaster.

Usage

1. For façades, framework, balconies, loggias, garages, and structures made from cellular concrete.
2. For living rooms, fireplace aprons, stairwells, corridors, kitchens, bathrooms and hobby rooms.

On walls. Indoors and outdoors.



WEISSES HAUS KUNSTHARZ-ROLLPUTZ:
Easy processing, visually appealing, permanent weather protection.

Substrates and preparation

The following applies to all substrates: Level, load-bearing, dust free, dry, free of oil and grease, free of separating impurities such as wallpaper paste. Compensate for interior unevenness with ROHBAUSPACHTEL INNEN, exterior unevenness with ROHBAUSPACHTEL AUSSEN. Fill cracks with RISS- UND FUGEN-ZU. Protect window frames and framework with masking tape.

Suitable substrates	Type of substrate/ Preparation	Priming
Coatings	adhesive, waterproof.	Prime substrates (except coatings) with BESTE BASIS or WEISSES HAUS SPERRGRUND.
Concrete	at least 4 weeks old, remove all form-work oil residue.	
Remove dust from	plasterboard, gypsum fibreboard and gypsum plasterboard.	
Gypsum plaster	at least 4 weeks old, remove gypsum skin.	
Pre-fill lime sandstone, cellular concrete and brickwork	with ROHBAUSPACHTEL INNEN in interior areas, with ROHBAUSPACHTEL AUSSEN in exterior areas, and allow to dry.	
Lime cement and cement plaster	at least 4 weeks old.	
Chipboard panels*	quality class P3 – P7 in accordance with DIN EN 312, installed in accordance with the manufacturer's instructions and the regulations.	
Unsuitable substrates		
Whitewash, distemper, OSB panels, wallpaper.		

*Chipboard is only suitable after priming with WEISSES HAUS SPERRGRUND.

Processing




1

Prime with BESTE BASIS or WEISSES HAUS SPERRGRUND. Allow to dry.



2

Stir the plaster with a stirrer. Apply a thin layer of ROLLPUTZ with a smoothing trowel (1-2 mm). Use rust-free tools.



3

Roll the fresh plaster within 10-20 minutes with a textured roller. Other textures can be created using a microfibre roller, paintbrush, bristle brush or sponge.



4

The texture is created immediately by rolling. Rolling texture variant: Ridges can be eradicated while fresh using a smoothing trowel.

Blending: The plaster can be blended with max. 2 % of spot colour. This creates pastel shades.
Painting over: Possible with emulsion paints after drying.

Product data

Consumption	approx. 1.5–2.2 kg/m ² /mm
Yield (20 kg)	9.1–13.3 m ² .
Processing/ substrate temperature	5–30 °C.
Open time	10–20 minutes
Drying time	1–3 days
Grain size	0.5 mm.
Ingredients	artificial resin, fillers, organic and inorganic additives. (Contains Benzisothiazolone (BIT). May cause allergic reactions.).
Package sizes	20 kg, 8 kg.
Shelf life	usable in original packaging until at least: See label. Store in a frost-free location. All times based on 20 °C and 65 % rel. humidity.

Please note

- | Coat contiguous surfaces without interruptions to avoid level differences.
- | Do not process if there is a risk of rain or in intense sunlight.
- | High humidity and low temperatures slow down hardening.
- | Do not use for coatings affected by standing water.
- | Contains natural grain. Colour shade fluctuations are therefore possible. Coat contiguous surfaces with material from the same manufacturing batch.

Health & safety:



Attention

Contains 2-Methyl-2H-isothiazol-3-on. May produce an allergic reaction. Contains 1,2-Benzisothiazol-3(2H)-on, reaction mass from: 5-Chlor-2-methyl-2H-isothiazol-3-on and 2-Methyl-2H-isothiazol-3-on (3:1). May produce an allergic reaction. If medical advice is necessary, keep the packaging or marking label ready. Keep out of the reach of children. Wear protective gloves / protective clothing / eye protection / face mask. Attention: Dangerous respirable droplets can occur when spraying. Do not inhale aerosol or mist. Take contents/container for disposal in accordance with the local and national regulations. A data sheet can be downloaded from the Internet at www.lugato.de.

If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: +49 (0)40 6 94 07-222.

The statements made in this information sheet reflect our current knowledge and experience. Since we do not have influence on the building-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products. For that reason in case of doubt, verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any oral consultation. The publication of this technical information sheet invalidates the previous editions. Subject to change without prior notice.



Responsible Care (RC) for the chemical industry means taking responsible action. It makes this clear through a worldwide initiative. In many countries, chemical associations run national RC programs. In the international initiative, thousands of companies are active with millions of employees. The goal is voluntary commitment to do more than just the compulsory: Promoting sustainability, demonstrating product responsibility, creating more safety for factories and the neighbourhood, improving health protection at the workplace and improving environmental protection. In the frame of its membership in the Verband der deutschen chemischen Industrie, LUGATO has committed itself to adhere to this objective.

Seminars

In cooperation with its trading associates, LUGATO is glad to pass on practical knowledge such as how to install tiles. Find more information about the current range of handyman seminars at www.lugato.de or at your local dealer.



EU: LUGATO GmbH & Co. KG, Großer Kamp 1,
D-22885 Barsbüttel, ☎ +49 (0)40 69407-0
Import /sales Schweiz: Puag AG, Oberebenestrasse 51,
CH-5620 Bremgarten, CH-Infoline: 0848 810 800

Copyright by LUGATO. Stand 11/2022

LUGATO