

BESTE BASIS Konzentrat



Deep primer for paints, plasters, adhesives and floor levelling compounds. Required for all absorbent sub-strates, e. g. gypsum building materials.

Product performance

- | Solvent-free primer concentrate with double coverage.
- | Cost effective through 1 : 1 dilution with water.
- | Penetrates deep into building materials.
- | Regulates the absorbency of building materials.
- | Dries quickly and colourlessly.
- | Extends the open time and thus the post-processing time of subsequent products.
- | Improves the adhesion of paints, plasters, adhesives, floor levelling compounds, wall fillers, wallpapers.
- | On floor, wall and ceiling. Indoor and outdoor use.
- | Very low emission (EMICODE EC 1) - therefore particularly suitable for indoor use.



Primes an absorbent plaster before subsequent work, e. g., painting.

Substrates and preparation

Suitable	anhydrite screeds, concrete, gypsum building boards, gypsum fibre boards, gypsum plasterboard, heated screeds (anhydrite or cement-bound), wooden floors, sand-lime brickwork, lime-cement, cement plaster, cellular concrete, chipboard, OSB boards, cement screeds. Observe the priming instructions for the respective LUGATO follow-up product, e. g. sealants, tile adhesives, floor levelling compounds, wall fillers, paints, synthetic resin plasters!
Consistency	absorbent, clean, load-bearing, not friable, dry, free of separating impurities.
Preparation	remove crumbly surfaces down to a sound substrate. Remove dust.

Processing



Dilute BESTE BASIS concentrate 1:1 with water.



Apply diluted with mop or brush. Avoid puddles and streak formation. Apply only so much BESTE BASIS that no glossy film is produced.

Product data

Quantity required	50-100 ml undiluted material/m ² , depending on the absorbency of the substrate.
Yield	50-100 m ² (5 l); 10-20 m ² (1 l).
Application / substrate temperature	5-30 °C.
Drying time	1-4 hours.
Ecology	solvent free. Very low emissions (EMICODE EC 1).
Ingredients	plastic dispersion, defoamer, preservative (Contains benzisothiazolone (BIT). May produce an allergic reaction.).
Package sizes	5 l, 1 l.
Shelf life	in original packaging at least: see label. Store in a frost-protected place. All times based on 15-20 °C and 65% rel. humidity.

Please note

- Protect adjacent surfaces from splashes.
- Protect primed surfaces from frost and rain until they are completely dry.

Health & safety:



Danger

Contains 2-Methyl-2H-isothiazol-3-on. May produce an allergic reaction. Contains 1,2-Benzisothiazol-3(2H)-on, reaction mass from: 5-Chlor-2-methyl-2H-isothiazol-3-on and 2-Methyl-2H-isothiazol-3-on (3:1). May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. Dispose of contents/container in accordance with local and national regulations. Safety data sheet can be downloaded on the Internet at www.lugato.com.

UFI: 2K25-XTE5-HG2H-JM4A

If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: +49 (0)40 6 94 07-222.

The statements made in this information sheet reflect our current knowledge and experience. Since we do not have influence on the building-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products.

For that reason in case of doubt, verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any oral consultation.

The publication of this technical information sheet invalidates the previous editions. Subject to change without prior notice.

EU: LUGATO GmbH & Co. KG, Großer Kamp 1,
D-22885 Barsbüttel, Tel.+49 (0)40 69407-0,
technik@lugato.de, www.lugato.de,
Import /sales Schweiz:
e + h Services AG, Industriestrasse 14,
CH-4658 Däniken, Tel.+41 62 288 61 11,
info@eh-services.ch, www.eh-services.ch

Copyright by LUGATO. Version 06/2026

LUGATO