LUGATO

HOLZ- & PARKETTFUGE



GEV-EMICODE EC 1 PLUS sehr emissionsarm

Seals connecting joints in parquet, timber floorboards and laminate, preventing penetration by dust, insects and cleaning water.

Product performance

- Solvent-free acrylic sealant in natural wood colours of maple, beech, oak, silver-grey oak and walnut.
- **Waterproof:** Protects wood from penetrating water, e.g. in skirting boards and at cut edges.
- **Silicone free:** does not cause adhesion problems in the parquet sealing.
- Can be sanded and painted over.

Applications

For sealing skirting joints and connecting joints e.g. at radiator pipes, expansion joints and door thresholds. In parquet, timber floorboards and laminate.

For indoor use.



HOLZ- & PARKETTFUGE: in a matching colour to the skirting.

Substrates and preparation

Suitability	Wood and all of the most popular materials, including metals and plastics.
Condition	Load-bearing, clean, grease-free, dry.
Preparation	Mask the edges of the joints with adhesive tape.

Processing

Inject sealant into the joint using the sealant gun. Smooth within 10 minutes with moistened FUGENGLÄTTER (with clear water). Remove adhesive tape and smooth the edges of the joint.

Product data

Consumption	approx. 25 ml/m with a 5 x 5 mm joint.
Coverage (310 ml)	approx. 12 m with a 5 x 5 mm joint.
Processing temperature	5–30 °C.
Joint width	5–30 mm.
Skin formation time	10-15 minutes
Can be sanded/treated	after 3 days.
Long-term elasticity:	10 %.
Ingredients	Artificial resin dispersion, modified natural resins, calcitic fillers, pigments, anti-frothing agents, thickening agents
Product characteristics	Fulfils the requirements of GEV-EMICODE® EC 1^{PLUS} for very low-emission products (further information available at www.emicode.com). No additional organic solvents.
Colours	maple, beech, oak, silver-grey oak, walnut.
Package size	310 ml.
	At least 50% of the cartridge (packaging) consists of recycled plastic (proportion of recycled material based on manufacturer specifications)
Storage life	Usable in original packaging until at least: See printing on package. Store in a frost-free location. All times based on 15–20 °C and 65 % rel. humidity. Higher temperatures reduce hardening time, lower temperatures increase hardening time.

Please note

Low temperatures and high humidity increase skin formation time. Unsuitable for effect of standing water. Do not bring into contact with bitumen. Use MARMOR + GRANIT SILICON for marble and natural stone.

Work safety: Not subject to labelling obligation in accordance with GHS.
GISCODE D1. Remove sealant with soap and water, do not allow to dry on the skin. If material gets into your eyes, flush thoroughly with water. Consult an eye specialist if necessary. The following applies with the antique white and silver-grey oak colours: Attention! Dangerous respirable droplets can occur when spraying. Do not inhale aerosol or mist. A data sheet can be downloaded from the Internet at www.lugato.de.

Disposal: Allow residual contents to harden and dispose of as domestic waste / construction site waste. Recycle empty packaging.

If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: +49 (0)40 6 94 07-222.

The statements made in this information sheet reflect our current knowledge and level of experience. Since we do not have influence on the object-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products.
For that reason, in case of doubt, verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any verbal consultation.
The publication of this technical information sheet invalidates all previous editions. Subject to change without prior notice.

EU: LUGATO GmbH & Co. KG, Großer Kamp 1,
D-22885 Barsbüttel, Tel.+49 (0)40 69407-0,
technik@lugato.de, www.lugato.de,
Import /sales Schweiz:
e + h Services AG, Industriestrasse 14,
CH-4658 Däniken, Tel.+41 62 288 61 11,
info@eh-services.ch, www.eh-services.ch

Copyright by LUGATO. Version 10/2026

LUGATO