Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Reglaced version: 2.8.0, issued: 10.10.2018 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Zementprodukte:

SICHERHEITSKLEBER FLEXIBEL PLUS

FUGENGRAU

SICHERHEITSKLEBER

FLEXKLEBER

FLEXKLEBER 420

FLIESENKLEBER 410

GROSSE KLASSE Spezialfliesenkleber

FLIESSBETTKLEBER 450

TROCK'NER KELLER DICHTUNGSSCHLÄMME

FLEX-FLIESENKLEBER C2T

PROFI-FLEXKLEBER

FLIESENKLEBER

GROSSFORMATKLEBER WAND & BODEN

FLEXKLEBER XXL 470

FLEXKLEBER C2T

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Chemical product for building, modernising and repairing.

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

LUGATO GmbH & Co. KG

Großer Kamp 1

D-22885 Barsbüttel

Telephone no. +49 (0)40 694 07-0 Fax no. +49 (0)40 694 07-109 + 110

Information provided by / telephone

Department TS, telephone +49 40 694 07-222

e-mail: technik@lugato.de

Advice on Safety Data Sheet

technik@lugato.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Reglaced version: 2.8.0, issued: 10.10.2018 Region: GB

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335

Classification information

Classification and labelling with respect to skin sensitization and/or respiratory sensitization are based on toxicological studies performed on the product (mixture).

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms





Signal word

Danger

Hazardous component(s) to be indicated on label:

Portland cement

Hazard statement(s)

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container to hazardous or special waste collection point.

Labelling information

These mixtures are considered to be low in chromate in accordance with EC-regulation 1907/2006, annex XVII (47). The proportion of water soluble chromate (VI) is below 2 ppm (mg/kg).

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Preparation containing hazardous components given in the following list.

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

Hazardous ingredients

No	Substance name		Additional information			
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conce	entration		%
	REACH no					
1	Portland cement					
	65997-15-1	Eye Dam. 1; H318	>	30.00 - <	50.00	%-b.w.
	266-043-4	Skin Irrit. 2; H315				
	-	STOT SE 3; H335				
	-	Skin Sens. 1; H317				
2	Portland cement, F	lue dust				
	68475-76-3	Eye Dam. 1; H318	>	1.00 - <	5.00	%-b.w.
	270-659-9	Skin Irrit. 2; H315				
	-	STOT SE 3; H335				
	01-2119486767-17	Skin Sens. 1; H317				
3	calcium diformate					
	544-17-2	Eye Dam. 1; H318	<	2.50		%-b.w.
	208-863-7					
	-					
	01-2119486476-24					

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off immediately with copious amounts of water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse out mouth and give plenty of water to drink. Seek medical advice immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Product itself is non-combustible; adapt fire extinguishing measures to surrounding areas.

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

No data available.

5.3 Advice for firefighters

Cement reacts strongly alkaline with water.

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid dust formation.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Product sets hard together with water, Take up mechanically. Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. Transport only in closed packing containers. Before use stand sacks upright and separate head piece (cover sheet) cleanly by cutting open. Carefully fill the powder, according to the instructions, into mixing vessels containing water. Avoid the formation and deposition of dust. Refer to protective measures listed in section 8.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Wash hands before breaks and after work.

Advice on protection against fire and explosion

No special measures necessary.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Store in a dry place. Protect from atmospheric moisture and water.

Requirements for storage rooms and vessels

Keep in original packaging, tightly closed.

Advice on storage assembly

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.
1	Portland cement	65997-15-1		266-043-4
	List of approved workplace exposure limits (WELs) / E	H40		
	Portland Cement			
	total inhalable dust			
	TWA	10	mg/m³	
	List of approved workplace exposure limits (WELs) / E	H40		
	Portland Cement			
	respirable dust		•	
	TWA	4	mg/m³	

Trade name: Zementprodukte:

Product no.: K-ZP

Current version : 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	calcium diformate			544-17-2	
				208-863-7	
	dermal	Short term (acut)	local	16.7	mg/cm ²
	dermal	Short term (acut)	systemic	4780	mg/kg/day
	dermal	Long term (chronic)	local	16.7	mg/cm ²
	dermal	Long term (chronic)	systemic	4780	mg/kg/day
	inhalative	Short term (acut)	systemic	337	mg/m³
	inhalative	Long term (chronic)	systemic	337	mg/m³

DNEL value (consumer)

No	Substance name		CAS / EC no		
	Route of exposure	Exposure time	Effect	Value	
1	calcium diformate			544-17-2	
				208-863-7	
	oral	Long term (chronic)	systemic	23.9	mg/kg/day
	dermal	Short term (acut)	local	8.3	mg/cm ²
	dermal	Short term (acut)	systemic	2390	mg/kg/day
	dermal	Long term (chronic)	systemic	2390	mg/kg/day
	dermal	Long term (chronic)	local	8.3	mg/cm ²
	inhalative	Long term (chronic)	local	8.3	mg/cm ²
	inhalative	Long term (chronic)	systemic	2390	mg/kg/day
	inhalative	Short term (acut)	systemic	83.2	mg/m³
	inhalative	Long term (chronic)	systemic	83.2	mg/m³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Туре	Value	
1	calcium diformate		544-17-2	
			208-863-7	
	water	fresh water	2	mg/L
	water	marine water	0.2	mg/L
	water	Aqua intermittent	10	mg/L
	water	marine water sediment	1.34	mg/kg
	with reference to: dry weight			
	water	fresh water sediment	13.4	mg/kg
	with reference to: dry weight			
	soil	-	1.5	mg/kg dry
				weight
	sewage treatment plant	-	2.21	mg/L

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. Short term: filter apparatus, Filter P2

Eye / face protection

Safety glasses with side protection shield (EN 166)

Trade name: Zementprodukte:

Product no.: K-ZP

Current version : 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material

Nitrile impregnated protective gloves

Other

Light protective clothing

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

information on basic physical and chemical properties				
Form/Colour				
Powder				
grey, white or coloured	grey, white or coloured			
Odour				
odourless	0.000			
Odour threshold				
No data available				
pH value	nH value			
Value	11.0 -	13.5		
Reference temperature	11.0	20	°C	
Remarks	Saturated solution			
Boiling point / boiling range				
No data available				
Melting point / melting range				
Value	>=	1200	°C	
Decomposition point / decomposition range				
No data available				
Flash point				
Not applicable				

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Reglaced version: 2.8.0, issued: 10.10.2018 Region: GB

Auto-ignition	temperature

No data available

Oxidising properties

No data available

Explosive properties

No data available

Flammability (solid, gas)

No data available

Lower flammability or explosive limits

No data available

Upper flammability or explosive limits

No data available

Vapour pressure

No data available

Vapour density

No data available

Evaporation rate

No data available

Relative density

No data available

Density

Value 2.9 - 3.2 g/cm³
Reference temperature 2.9 °C

Bulk density

Value appr. 1100 kg/m³

Solubility in water

Value appr. 1.5 g/l Reference temperature 20 °C

Solubility(ies)

No data available

Partition coefficient: n-octanol/water

No data available

Viscosity

No data available

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Reglaced version: 2.8.0, issued: 10.10.2018 Region: GB

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity
No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No Product Name

1 Zementprodukte:

SICHERHEITSKLEBER FLEXIBEL PLUS

FUGENGRAU

SICHERHEITSKLEBER

FLEXKLEBER

FLEXKLEBER 420

FLIESENKLEBER 410

GROSSE KLASSE Spezialfliesenkleber

FLIESSBETTKLEBER 450

TROCK'NER KELLER DICHTUNGSSCHLÄMME

FLEX-FLIESENKLEBER C2T

PROFI-FLEXKLEBER

FLIESENKLEBER

GROSSFORMATKLEBER WAND & BODEN

FLEXKLEBER XXL 470

FLEXKLEBER C2T

Route of exposure	Skin
Evaluation/classification	Based on available data, the classification criteria are not met

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Reglaced version: 2.8.0, issued: 10.10.2018 Region: GB

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

Symptoms related to the physical, chemical and toxicological characteristics

The product can cause skin and eye irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation may lead to irritation of the respiratory tract.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge into the drains or waters and do not store on public depositories.

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Completely emptied packagings can be given for recycling. Packaging that cannot be cleaned should be disposed of in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

Trade name: Zementprodukte:

Product no.: K-ZP

Current version: 2.9.0, issued: 18.10.2018 Replaced version: 2.8.0, issued: 10.10.2018 Region: GB

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H317 May cause an allergic skin reaction.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 20275