

BAUSCHAUM-REINIGER



For removing fresh PU foam remnants.

Product performance

- | Highly effective solvent.
- | Removes fresh PU foam contamination e.g. from windows and doors without a trace.
- | Creates fat-free subsurfaces e.g. before the application of adhesives and paintings.

Application

1. Removes fresh PU foam remnants from door frames, window frames and tools.
2. Cleans valves and adapters of PU foam tins during work interruptions.
3. Defats building materials and metals, e.g. tiles, tools.

Substrates and preparation

Suitable	Mineral construction materials, ceramics, glass, enamels, metals.
Unsuitable	Surfaces vulnerable to acetone.
Preparation	Cover adjacent areas e.g. with adhesive tape or foil. Wipe off foam remnants as far as possible with a cloth.

Processing

Keep the tin upright and spray its content on the soiled areas. Immediately wipe with a clean cloth.

Product data

Processing temperature	0–30 °C (41–86 °F).
Ingredients	Acetone, isopropyl, propellant.
Pack size	150 ml.
Shelf life	At least 24 months in original packaging.

Please note

- | Test the compatibility with sensible surfaces such as plastics, varnishes in preliminary tests.
- | Hardened foam remnants can only be removed mechanically.

Health & safety:



Acetone. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Request safety data sheet if needed or download from the Internet at www.lugato.de in German.



Danger

Disposal: Recycle can completely empty.

The statements made in this information sheet reflect our current knowledge and experience. Since we do not have influence on the object-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products.

For that reason, in case of doubt verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any oral consultation.

The publication of this technical information sheet invalidates the previous editions. Subject to change without prior notice.



Responsible Care (RC) for the chemical industry means taking responsible action. This is made clear through a worldwide initiative. In many countries, chemical associations run national RC programs. In the international initiative, thousands of companies are active with millions of employees. The goal is voluntary commitment to do more than just the compulsory: Promoting sustainability, demonstrating product responsibility, creating more safety for factories and the neighbourhood, improving health protection at the workplace and improving environmental protection. In the frame of its membership in the Verband der deutschen chemischen Industrie, LUGATO has committed itself to adhere to this objective.

If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: (040) 6 94 07-222.

Seminars

In cooperation with its trading associates, LUGATO is glad to pass on practical knowledge such as how to install tiles. Find more information about the current range of handyman seminars at www.lugato.de or at your local dealer.



SIMPLY DO IT YOURSELF

Ask your retailer about the "SIMPLY DO IT YOURSELF" brochure. On more than 160 pages with over 1000 illustrations from "Gluing Tiles" to "Sealing Buildings". All instructions are simply explained picture-by-picture.



LUGATO GmbH & Co. KG, D - 22885 Barsbüttel,
Technical Service Tel.: +49 (0)40 69 40 7 - 222, technik@lugato.de
www.lugato.com

Copyright by LUGATO. Version 07/2017

